

Safety Data Sheet

Material Name: L-5X: 404-13-RS03

*** Section 1 - Product and Company Identification ***

Manufacturer Information

KNS Companies
475 Randy Road
Carol Stream, IL 60188-0762

Phone: 630-665-9010

Emergency # 800-424-9300 (CHEMTREC-24hr.)

*** Section 2 - Hazards Identification ***

GHS Classification:

Flammable Liquids - Category 2
Acute Toxicity Oral - Category 4
Acute Toxicity Dermal - Category 4
Acute Toxicity Inhalation - Category 4
Skin Irritation - Category 2
Eye Damage/Irritation - Category 2A
Germ Cell Mutagenicity - Category 2
Carcinogenicity - Category 1A
Specific Target Organ Toxicity Single Exposure - Category 3
Hazardous to the Aquatic Environment Acute - Category 1
Hazardous to the Aquatic Environment Chronic - Category 1

GHS LABEL ELEMENTS

Symbol(s)



Signal Word

Danger

Hazard Statements

H225: Highly flammable liquid and vapor.
H302: Harmful if swallowed.
H312: Harmful in contact with skin.
H332: Harmful if inhaled.
H318: Causes severe eye damage.
H317: May cause an allergic skin reaction.
H340: May cause genetic defects.
H350: May cause cancer.
H336: May cause drowsiness or dizziness.
H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Safety Data Sheet

Material Name: L-5X: 404-13-RS03

- P233: Keep container tightly closed.
- P240: Ground/bond container and receiving equipment.
- P241: Use explosion-proof electrical/ventilating/lighting equipment.
- P242: Use only non-sparking tools.
- P243: Take precautionary measures against static discharge.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P264: Wash thoroughly after handling.
- P270: Do not eat, drink or smoke when using this product.
- P260: Do not breathe fume/gas/mist/vapors/spray.
- P272: Contaminated clothing must not be allowed out of the workplace.
- P271: Use only outdoors or in a well-ventilated area.
- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P273: Avoid release to the environment.

Response

- P370+378: In case of fire: Use water, fog, alcohol foam, CO₂, dry chemical to extinguish.
- P303+361+353+363: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.
- P333+313: If skin irritation or rash occurs: Get medical advice/attention.
- P304+340+310: If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor.
- P305+351+338: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+313: If exposed or concerned: Get medical advice/attention.

Storage

- P403+233+235: Store in a well-ventilated place. Keep cool. Keep container tightly closed.
- P405: Store locked up.

Disposal

- P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

* * * Section 3 - Composition / Information on Ingredients * * *

CAS #	Component	Percent
67-64-1	Acetone	4-6
111-76-2	2-Butoxyethanol	10-11
64-17-5	Ethyl alcohol	8-9
67-63-0	Isopropyl alcohol	0.5-1
78-83-1	Isobutyl alcohol	8-10
108-95-2	Phenol	4-5
71-36-3	1-Butanol	2-3
7664-38-2	Phosphoric acid	0.5-0.6
50-00-0	Formaldehyde	0.2-0.4

Safety Data Sheet

Material Name: L-5X: 404-13-RS03

*** Section 4 - First Aid Measures ***

First Aid: Eyes

Flush immediately with water for at least 15 minutes. Get prompt medical attention.

First Aid: Skin

Remove contaminated clothing. Keep away from ignition sources. Flush skin thoroughly with soap and water for 15 minutes. Get medical attention if irritation persists.

First Aid: Ingestion

Rinse mouth. Drink water and do not induce vomiting. If material enters lungs, remove person to fresh air and administer artificial respiration if not breathing. Seek immediate medical attention.

First Aid: Inhalation

Remove person to fresh air. Administer artificial respiration if not breathing. Get immediate medical attention.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.

Flammable liquid. Vapors are heavier than air and may travel considerable distances to ignition sources and flash back or explode. Empty containers are dangerous due to residual flammable vapors. Do not cut, grind, or weld on or near empty containers until thoroughly cleaned. Obey label precautions, especially during drum cleaning.

Wash containers thoroughly with soap and water before handling, reuse, or disposal.

Hazardous Combustion Products

No data available

Extinguishing Media

Water, fog, alcohol foam, CO2, dry chemical

Unsuitable Extinguishing Media

None

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

*** Section 6 - Accidental Release Measures ***

Recovery and Neutralization

Stop the flow of material, if this is without risk.

Materials and Methods for Clean-Up

Remove all sources of ignition. Provide strong ventilation. Clean up small spills with absorbent material and put in closed containers. Larger spills should be contained and transferred to closed containers.

Emergency Measures

Isolate area. Keep unnecessary personnel away.

Personal Precautions and Protective Equipment

Response personnel should use eye and skin protection and respirators.

Environmental Precautions

Prevent run-off from entering drains or streams.

Prevention of Secondary Hazards

None

Safety Data Sheet

Material Name: L-5X: 404-13-RS03

*** Section 7 - Handling and Storage ***

Handling Procedures

Use in a well-ventilated area. Avoid skin and eye exposure. Wash thoroughly after handling.

Storage Procedures

Keep away from heat and ignition sources. Containers should be grounded to prevent static sparks during transfer and pouring.

Incompatibilities

No data available

*** Section 8 - Exposure Controls / Personal Protection ***

Component Exposure Limits

Acetone (67-64-1)

ACGIH: 500 ppm TWA
750 ppm STEL
OSHA: 1000 ppm TWA; 2400 mg/m³ TWA
NIOSH: 250 ppm TWA; 590 mg/m³ TWA

Ethyl alcohol (64-17-5)

ACGIH: 1000 ppm STEL
OSHA: 1000 ppm TWA; 1900 mg/m³ TWA
NIOSH: 1000 ppm TWA; 1900 mg/m³ TWA

2-Butoxyethanol (111-76-2)

ACGIH: 20 ppm TWA
OSHA: 50 ppm TWA; 240 mg/m³ TWA
prevent or reduce skin absorption
NIOSH: 5 ppm TWA; 24 mg/m³ TWA
Potential for dermal absorption

Isobutyl alcohol (78-83-1)

ACGIH: 50 ppm TWA
OSHA: 100 ppm TWA; 300 mg/m³ TWA
NIOSH: 50 ppm TWA; 150 mg/m³ TWA

Phenol (108-95-2)

ACGIH: 5 ppm TWA
Skin - potential significant contribution to overall exposure by the cutaneous route
OSHA: 5 ppm TWA; 19 mg/m³ TWA
prevent or reduce skin absorption
NIOSH: 5 ppm TWA; 19 mg/m³ TWA
15.6 ppm Ceiling (15 min); 60 mg/m³ Ceiling (15 min)
Potential for dermal absorption

Safety Data Sheet

Material Name: L-5X: 404-13-RS03

1-Butanol (71-36-3)

ACGIH: 20 ppm TWA
OSHA: 100 ppm TWA; 300 mg/m³ TWA
NIOSH: 50 ppm Ceiling; 150 mg/m³ Ceiling
Potential for dermal absorption

Isopropyl alcohol (67-63-0)

ACGIH: 200 ppm TWA
400 ppm STEL
OSHA: 400 ppm TWA; 980 mg/m³ TWA
NIOSH: 400 ppm TWA; 980 mg/m³ TWA
500 ppm STEL; 1225 mg/m³ STEL

Phosphoric acid (7664-38-2)

ACGIH: 1 mg/m³ TWA
3 mg/m³ STEL
OSHA: 1 mg/m³ TWA
NIOSH: 1 mg/m³ TWA
3 mg/m³ STEL

Formaldehyde (50-00-0)

ACGIH: 0.3 ppm Ceiling
OSHA: 2 ppm STEL (Irritant and potential cancer hazard, See 29 CFR 1910.1048, 15 min); 0.5 ppm
Action Level; 0.75 ppm TWA
0.75 ppm TWA
2 ppm STEL (see 29 CFR 1910.1048)
NIOSH: 0.016 ppm TWA
0.1 ppm Ceiling (15 min)

Engineering Measures

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Personal Protective Equipment: Respiratory

If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Personal Protective Equipment: Hands

Wear solvent-resistant protective gloves, and other impervious body protection if needed.

Personal Protective Equipment: Eyes

Wear safety glasses; chemical goggles (if splashing is possible).

Personal Protective Equipment: Skin and Body

Work clothing sufficient to prevent all skin contact should be worn, such as coveralls and long sleeves.

Safety Data Sheet

Material Name: L-5X: 404-13-RS03

*** Section 9 - Physical & Chemical Properties ***

Appearance:	opaque, colored, viscous	Odor:	paint solvent
Physical State:	liquid	pH:	no data available
Vapor Pressure:	no data available	Vapor Density:	>1 (air=1)
Boiling Point:	no data available	Melting Point:	no data available
Solubility (H2O):	slight	Specific Gravity:	1.13 -1.19
Evaporation Rate:	no data available	Bulk Density:	9.72 +/- 0.20 lb./gal
Viscosity:	18 - 20 (# 4FC 70°F (sec.))	Flash Point:	80°F (26.6°C)
Flash Point Method:	ASTM 3278	Upper Flammability Limit (UFL):	13
Lower Flammability Limit (LFL):	1	Burning Rate:	no data available
Auto Ignition:	no data available		

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

This is a stable material.

Hazardous Reaction Potential

Will not occur

Conditions to Avoid

Ignition sources

Incompatible Products

No data available

Hazardous Decomposition Products

No data available

*** Section 11 - Toxicological Information ***

Acute Toxicity

Component Analysis - LD50/LC50

Acetone (67-64-1)

Oral LD50 Rat 5800 mg/kg

Dimethyl carbonate (616-38-6)

Inhalation LC50 Rat 140 mg/L 4 h; Oral LD50 Rat 13000 mg/kg; Dermal LD50 Rat >2500 mg/kg; Dermal LD50 Rabbit >5 g/kg

Ethyl alcohol (64-17-5)

Oral LD50 Rat 7060 mg/kg; Inhalation LC50 Rat 124.7 mg/L 4 h

2-Butoxyethanol (111-76-2)

Inhalation LC50 Rat 2.21 mg/L 4 h; Inhalation LC50 Rat 450 ppm 4 h; Oral LD50 Rat 470 mg/kg; Dermal LD50 Rat 2270 mg/kg; Dermal LD50 Rabbit 220 mg/kg

Safety Data Sheet

Material Name: L-5X: 404-13-RS03

Isobutyl alcohol (78-83-1)

Inhalation LC50 Rat >6.5 mg/L 4 h; Oral LD50 Rat 2460 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

Phenol (108-95-2)

Oral LD50 Rat 317 mg/kg; Dermal LD50 Rat 525 mg/kg; Dermal LD50 Rabbit 630 mg/kg; Inhalation LC50 Rat 316 mg/m³ 4 h

1-Butanol (71-36-3)

Inhalation LC50 Rat >17.7 mg/L 4 h; Inhalation LC50 Rat 8000 ppm 4 h; Oral LD50 Rat 790 mg/kg; Dermal LD50 Rabbit 3400 mg/kg

Isopropyl alcohol (67-63-0)

Inhalation LC50 Rat 72.6 mg/L 4 h; Oral LD50 Rat 4396 mg/kg; Dermal LD50 Rat 12800 mg/kg; Dermal LD50 Rabbit 12870 mg/kg

Phosphoric acid (7664-38-2)

Inhalation LC50 Rat >850 mg/m³ 1 h; Oral LD50 Rat 1530 mg/kg; Dermal LD50 Rabbit 2730 mg/kg

Formaldehyde (50-00-0)

Oral LD50 Rat 500 mg/kg; Inhalation LC50 Rat 0.578 mg/L 4 h; Inhalation LC50 Rat 1000 mg/m³ 30 min

Potential Health Effects: Eye Critical Damage/ Stimulativeness

Liquid causes irritation and possible eye damage.

Potential Health Effects: Ingestion

May cause irritation in mouth and throat, and stomach disturbances. Large amounts can be fatal.

Potential Health Effects: Inhalation

Vapors can cause headache, dizziness, irritation of nose and throat. Excessive amounts can cause asphyxiation.

Respiratory Organs Sensitization/Skin Sensitization

May cause an allergic skin reaction

Generative Cell Mutagenicity

Suspected of causing genetic defects

Carcinogenicity

A: General Product Information

May cause cancer

Formaldehyde vapors cause cancer in the nasal passages of animals in laboratory tests. There is limited evidence of its causing cancer in humans. While the percentage of formaldehyde is very low (< 1%) in this product, it is recommended that good ventilation be used during use and that appropriate respirator protection be used when vapor concentrations exceed the OSHA Permissible Exposure Limit (PEL).

B: Component Carcinogenicity

Acetone (67-64-1)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

Safety Data Sheet

Material Name: L-5X: 404-13-RS03

Ethyl alcohol (64-17-5)

ACGIH: A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC: Monograph 100E [2012] (in alcoholic beverages); Monograph 96 [2010] (in alcoholic beverages)
(Group 1 (carcinogenic to humans))

2-Butoxyethanol (111-76-2)

ACGIH: A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC: Monograph 88 [2006] (Group 3 (not classifiable))

Phenol (108-95-2)

ACGIH: A4 - Not Classifiable as a Human Carcinogen
IARC: Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable))

Formaldehyde (50-00-0)

ACGIH: A2 - Suspected Human Carcinogen
OSHA: 2 ppm STEL (Irritant and potential cancer hazard, See 29 CFR 1910.1048, 15 min); 0.5 ppm
Action Level; 0.75 ppm TWA
NIOSH: potential occupational carcinogen
NTP: Known Human Carcinogen (Select Carcinogen)
IARC: Monograph 100F [2012]; Monograph 88 [2006]; Monograph 62 [1995]; Supplement 7 [1987]
(Group 1 (carcinogenic to humans))

Reproductive Toxicity

This product is not reported to have any reproductive toxicity effects.

Specified Target Organ General Toxicity: Single Exposure

May cause drowsiness or dizziness.

Specified Target Organ General Toxicity: Repeated Exposure

This product is not reported to have any specific target organ toxicity repeat exposure effects.

Aspiration Respiratory Organs Hazard

Not an aspiration hazard.

* * * Section 12 - Ecological Information * * *

Ecotoxicity

A: General Product Information

Very toxic to aquatic life with long lasting effects.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Acetone (67-64-1)

Test & Species

96 Hr LC50 Oncorhynchus mykiss	4.74 - 6.33 mL/L
96 Hr LC50 Pimephales promelas	6210 - 8120 mg/L [static]
96 Hr LC50 Lepomis macrochirus	8300 mg/L
48 Hr EC50 Daphnia magna	10294 - 17704 mg/L [static]
48 Hr EC50 Daphnia magna	12600 - 12700 mg/L

Safety Data Sheet

Material Name: L-5X: 404-13-RS03

Ethyl alcohol (64-17-5)

Test & Species

96 Hr LC50 Oncorhynchus mykiss	12.0 - 16.0 mL/L [static]
96 Hr LC50 Pimephales promelas	>100 mg/L [static]
96 Hr LC50 Pimephales promelas	13400 - 15100 mg/L [flow-through]
48 Hr LC50 Daphnia magna	9268 - 14221 mg/L
24 Hr EC50 Daphnia magna	10800 mg/L
48 Hr EC50 Daphnia magna	2 mg/L [static]

2-Butoxyethanol (111-76-2)

Test & Species

96 Hr LC50 Lepomis macrochirus	1490 mg/L [static]
96 Hr LC50 Lepomis macrochirus	2950 mg/L
24 Hr EC50 Daphnia magna	1698 - 1940 mg/L
48 Hr EC50 Daphnia magna	>1000 mg/L

Isobutyl alcohol (78-83-1)

Test & Species

96 Hr LC50 Pimephales promelas	1370-1670 mg/L [flow-through]
96 Hr LC50 Pimephales promelas	375 mg/L [static]
96 Hr LC50 Lepomis macrochirus	1480-1730 mg/L [flow-through]
96 Hr LC50 Oncorhynchus mykiss	1120-1520 mg/L [flow-through]
48 Hr EC50 Desmodemus subspicatus	230 mg/L
48 Hr EC50 Daphnia magna	1300 mg/L
48 Hr EC50 Daphnia magna	1070 - 1933 mg/L [static]

Phenol (108-95-2)

Test & Species

96 Hr LC50 Pimephales promelas	11.9-50.5 mg/L [flow-through]
96 Hr LC50 Pimephales promelas	20.5-25.6 mg/L [static]
96 Hr LC50 Pimephales promelas	32 mg/L
96 Hr LC50 Oncorhynchus mykiss	5.449-6.789 mg/L [flow-through]
96 Hr LC50 Oncorhynchus mykiss	7.5-14 mg/L [static]
96 Hr LC50 Oncorhynchus mykiss	4.23-7.49 mg/L [semi-static]
96 Hr LC50 Oncorhynchus mykiss	5.0-12.0 mg/L
96 Hr LC50 Lepomis macrochirus	13.5 mg/L [static]
96 Hr LC50 Lepomis macrochirus	11.9-25.3 mg/L [flow-through]

Safety Data Sheet

Material Name: L-5X: 404-13-RS03

96 Hr LC50 Lepomis macrochirus	11.5 mg/L [semi-static]
96 Hr LC50 Poecilia reticulata	34.09-47.64 mg/L [static]
96 Hr LC50 Poecilia reticulata	31 mg/L [semi-static]
96 Hr LC50 Brachydanio rerio	27.8 mg/L
96 Hr LC50 Cyprinus carpio	0.00175 mg/L [semi-static]
96 Hr LC50 Oryzias latipes	33.9-43.3 mg/L [flow-through]
96 Hr LC50 Oryzias latipes	23.4-36.6 mg/L [static]
96 Hr EC50 Pseudokirchneriella subcapitata	46.42 mg/L
96 Hr EC50 Pseudokirchneriella subcapitata	0.0188 - 0.1044 mg/L [static]
72 Hr EC50 Desmodesmus subspicatus	187 - 279 mg/L [static]
48 Hr EC50 Daphnia magna	4.24 - 10.7 mg/L [static]
48 Hr EC50 Daphnia magna	10.2 - 15.5 mg/L

1-Butanol (71-36-3)

Test & Species

96 Hr LC50 Pimephales promelas	1730-1910 mg/L [static]
96 Hr LC50 Pimephales promelas	1740 mg/L [flow-through]
96 Hr LC50 Lepomis macrochirus	100000-500000 µg/L [static]
96 Hr LC50 Pimephales promelas	1910000 µg/L [static]
96 Hr EC50 Desmodesmus subspicatus	>500 mg/L
72 Hr EC50 Desmodesmus subspicatus	>500 mg/L
48 Hr EC50 Daphnia magna	1983 mg/L
48 Hr EC50 Daphnia magna	1897 - 2072 mg/L [Static]

Isopropyl alcohol (67-63-0)

Test & Species

96 Hr LC50 Pimephales promelas	9640 mg/L [flow-through]
96 Hr LC50 Pimephales promelas	11130 mg/L [static]
96 Hr LC50 Lepomis macrochirus	>1400000 µg/L
96 Hr EC50 Desmodesmus subspicatus	>1000 mg/L
72 Hr EC50 Desmodesmus subspicatus	>1000 mg/L

Safety Data Sheet

Material Name: L-5X: 404-13-RS03

Phosphoric acid (7664-38-2)

Test & Species

96 Hr LC50 Gambusia affinis	3 - 3.5 mg/L
12 Hr EC50 Daphnia magna	4.6 mg/L

Formaldehyde (50-00-0)

Test & Species

96 Hr LC50 Pimephales promelas	22.6 - 25.7 mg/L [flow-through]
96 Hr LC50 Lepomis macrochirus	1510 µg/L [static]
96 Hr LC50 Brachydanio rerio	41 mg/L [static]
96 Hr LC50 Oncorhynchus mykiss	0.032 - 0.226 mL/L [flow-through]
96 Hr LC50 Oncorhynchus mykiss	100 - 136 mg/L [static]
96 Hr LC50 Pimephales promelas	23.2 - 29.7 mg/L [static]
48 Hr LC50 Daphnia magna	2 mg/L
48 Hr EC50 Daphnia magna	11.3 - 18 mg/L [static]

Persistence/Degradability

No information available for the product.

Bioaccumulation

No information available for the product.

Mobility in Soil

No information available for the product.

* * * Section 13 - Disposal Considerations * * *

Waste Disposal Instructions

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

Disposal of Contaminated Containers or Packaging

Dispose of contents/container in accordance with local/regional/national/international regulations.

* * * Section 14 - Transportation Information * * *

DOT Information

Shipping Name: Paint

UN #: 1263 Hazard Class: 3 Packing Group: II

* * * Section 15 - Regulatory Information * * *

Regulatory Information

US Federal Regulations

Safety Data Sheet

Material Name: L-5X: 404-13-RS03

Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

Acetone (67-64-1)

CERCLA: 5000 lb final RQ; 2270 kg final RQ

Isobutyl alcohol (78-83-1)

CERCLA: 5000 lb final RQ; 2270 kg final RQ

Phenol (108-95-2)

SARA 302: 500 lb lower TPQ; 10000 lb upper TPQ

SARA 313: 1.0 % de minimis concentration

CERCLA: 1000 lb final RQ; 454 kg final RQ

1-Butanol (71-36-3)

SARA 313: 1.0 % de minimis concentration

CERCLA: 5000 lb final RQ; 2270 kg final RQ

Phosphoric acid (7664-38-2)

CERCLA: 5000 lb final RQ; 2270 kg final RQ

Formaldehyde (50-00-0)

SARA 302: 500 lb TPQ

SARA 313: 0.1 % de minimis concentration

CERCLA: 100 lb final RQ; 45.4 kg final RQ

State Regulations

Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Acetone	67-64-1	Yes	Yes	Yes	Yes	Yes	No
Dimethyl carbonate	616-38-6	No	Yes	No	Yes	Yes	No
Ethyl alcohol	64-17-5	Yes	Yes	Yes	Yes	Yes	No
2-Butoxyethanol	111-76-2	Yes	Yes	Yes	Yes	Yes	No
Isobutyl alcohol	78-83-1	Yes	Yes	Yes	Yes	Yes	No
Phenol	108-95-2	Yes	Yes	Yes	Yes	Yes	No
1-Butanol	71-36-3	Yes	Yes	Yes	Yes	Yes	No
Phosphoric acid	7664-38-2	Yes	Yes	Yes	Yes	Yes	No
Formaldehyde	50-00-0	Yes	Yes	Yes	Yes	Yes	No

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer.

Safety Data Sheet

Material Name: L-5X: 404-13-RS03

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects.

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Acetone	67-64-1	1 %
Ethyl alcohol	64-17-5	0.1 %
2-Butoxyethanol	111-76-2	1 %
Isobutyl alcohol	78-83-1	1 %
Phenol	108-95-2	1 %
1-Butanol	71-36-3	1 %
Formaldehyde	50-00-0	0.1 %

Additional Regulatory Information

Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Acetone	67-64-1	Yes	DSL	EINECS
Dimethyl carbonate	616-38-6	Yes	DSL	EINECS
Ethyl alcohol	64-17-5	Yes	DSL	EINECS
2-Butoxyethanol	111-76-2	Yes	DSL	EINECS
Isobutyl alcohol	78-83-1	Yes	DSL	EINECS
Phenol	108-95-2	Yes	DSL	EINECS
1-Butanol	71-36-3	Yes	DSL	EINECS
Phosphoric acid	7664-38-2	Yes	DSL	EINECS
Formaldehyde	50-00-0	Yes	DSL	EINECS

* * * Section 16 - Other Information * * *

Key/Legend

EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration, NJTSR = New Jersey Trade Secret Registry.

Literature References

None

Other Information

The information herein has been compiled from sources believed to be reliable and is accurate to the best of our knowledge. However, KNS Companies, Inc. cannot give any guarantees regarding information from other sources, and expressly does not make any warranties, nor assume any liability, for its use.

End of Sheet